



VIBROSCREEN

Portable screeners

by **VT** | VIBROTECH

Increase value of your material



SCM-75C

Up to 6 cubic yards bucket



Great quality, great value !

- Heavy Duty construction
- Portable equipment
- Up to 300 cubic yards per hour
- Low maintenance
- Reversible shakerhead for better screening effect
- Quick screen change

www.vibroscreen.ca

819 362-8871



VIBROSCREEN

Portable screeners

by **VT** | **VIBROTECH**

MODEL SCM-75C

(Up to 300 cubic yards / hour)

CAPACITY

Maximum single load	Up to 6 cubic yards
Cycle time, average	30 seconds
Shaker head decks	2
Screening area	119" x 90" (75 sq-ft)

TOWING

Hitch type	Fifth wheel
Axle type	Single axle, double wheels
Suspension	None
Brakes	Air
Landing gear	Hydraulic
Lights and mud flaps	Included

ENGINE

Manufacturer	Perkins
Type	Diesel, vertical, water cooled
Tank	141 liters (38 gal)
Fuel autonomy	Up to 9 hours
Power	90 HP
Number of cylinders	4
Cold starting aid	Glow plug
Electric starter	Included
Alternator	Included

OPTIONS AVAILABLE

Wings plates extensions	Wear plate (over's side)
Hydraulic grizzly	Punch plate (top screen)
Flexmat screen	

WEIGHT

Gross weight	27 500 lbs (12,500 kg)
Tongue weight	9460 lbs (4300 kg)

HYDRAULICS

Control valves	Shakerhead (forward - reverse) Front jack cylinder Axle cylinder Conveyor (start-stop, open-close)
Cooling	Hydraulic cooler

WARRANTY

Equipment	12 months
-----------	-----------

WORKING DIMENSIONS


Loading height	11' - 0"
Hopper width (feeding)	12' - 6"
Working length	48' - 10"
Free height (under conveyor)	10' - 1"
Discharge belt width	42"

FREIGHT DIMENSIONS

Total height on wheel	11' - 11"
Total length	37' - 5"
Total width	8' - 8"




Hydraulic grizzly



Punch plates (top screen)



Wings plates extensions



Wear plate (over's side)